



Translucent

Available Colours

White	00.02	
Sand	00.10	
Dusk	00.15	
Linen	00.20	
Stone	00.22	
Mushroom	00.55	
Suede	00.71	
Pewter	00.01	
Onyx	00.30	

Fabric Specifications

Stock Widths	118"
Openness Factor	5%
Composition	100% Polyester / PVC Free 89% Recycled Content
Thickness	.017"
Weight	5.01/ oz/sq yrd
Fire Rating	NFPA 701-04TM#1, California U.S. Title 19
Cleaning Instructions	Contact Manufacturer
Spline	Yes
Railroaded	No



Mermet's "Fabrics for Life™" begin with everyday life in mind, whether at home, in the office, hospitality or healthcare. Our state-of-the-art weaving process creates designer fabrics which function beautifully to maintain the view while efficiently managing the effects of the sun.

Mermet offers over 500 fabric options for interior and exterior applications, ranging from transparent, to translucent, to blackout. A variety of openness factors from 0% to 14% offer varying degrees of privacy, view through, glare control and heat protection.

Mermet's innovative, functional fabrics are designed for solar protection, energy savings, pleasing visual aesthetics and acoustical comfort. Mermet fabrics are GREENGUARD® certified and fire rated to NFPA 701 standards.

- Bacterial and Fungal Resistance: ASTM E2180 and ASTM G21
- If you require additional fabric send E-mail to: samples@frasershading.com
- Actual fabric colours may vary from pictures, Fabric stock levels may vary.
- Openness factors are approximate. Mockups are recommended. Specification subject to change without notice. ©Fraser Shading Systems 2017



GreenScreen Revive® 5%

Product Type: Interior - Translucent

Fenestration Properties

Description	Colour	SHGC/G Value					
		T _s	R _s	A _s	T _v	CL-S	DG
02.02	White	38	56	6	37	0.44	0.39
00.10	Sand	35	54	11	33	0.44	0.40
00.15	Dusk	22	31	47	8	0.56	0.47
00.20	Linen	32	52	16	28	0.45	0.41
00.22	Stone	27	49	24	20	0.46	0.41
00.55	Mushroom	27	42	31	18	0.50	0.44
00.71	Suede	25	35	40	13	0.54	0.46
00.01	Pewter	26	37	37	14	0.53	0.45
00.30	Onyx	22	31	47	9	0.56	0.47

KEY: The fenestration property tests were conducted in accordance with EN 14501:2005, ASTM 891, ASTM E903-96: Shading Coefficient (SC), Solar Heat Gain Coefficient (SHGC), Solar Transmittance (T_s), Solar Reflectance (R_s), Solar Absorptance (A_s), Visible Light Transmittance (T_v); ¼ (6mm) Clear Glass (CL); 4mm Clear Glass, Single Glazing (CL-S); Double Glazing 4mm/16mm/4mm with low E-coating in position 3, space filled with Argon (DG); To calculate shading coefficient: SHGC CL-S / 0.87. Acoustical performance tested in accordance with ASTM C423-09a: NRC is Noise Reduction Coefficient, SAA is Sound Absorption Average. The above data is indicative.

Specifications:

Composition:	100% Polyester / PVC Free (89% Recycled Content)
Openness factor:	Approximately 5%
Weight:	5.01 oz / yd ² (170 g / m ²) + 5%
Thickness:	0.017" (0.44 mm) + 5%
Accoustical Performance:	NRC: 0.25, SAA: 0.24