



SW2360 Series

' H Q V H % D V N H W : H D Y H

Fire Rated

Available Colours

Oyster	P12
Oyster/Beige	P13
Oyster/Pearl Gray	P14
Beige	Q20
Beige/Pearl Gray	Q21
Pearl Gray	V20
Charcoal	V21
Charcoal/Gray	V22
Charcoal/Chestnut	V24
Charcoal/Alpaca	V32

) D E U L F 6 S H F L ¿ F D W L R

Stock Widths	72"/96"
Openness Factor	10%
Composition	35% Fiberglass 65% Vinyl on Fiberglass
Thickness	.017"
Weight	10.5 oz/sq yrd
Fire Rating	NFPA 701-2004 /CA US Title 19
Cleaning Instructions	Contact Manufacturer
Spline	Yes
Railroaded	Not Recommended

Manufactured with ease of fabrication in mind, Styles 2390, 2360, 2410, and 2500 are thin and openess factors to meet the broadest range of performance in a non-directional fabric. Styles 2390/2360/2410/2500 can also be used for exterior roller shades.

‡ ASTM E2180, ASTM 22 AATCC30 Part 3, ASTM G21, ASTM D3273, GREENGUARD Mold & Bacteria Standard ASTM 6329

‡ If you require additional fabric send E-mail to: samples@frasershading.com

‡ Actual fabric colours may vary from pictures, Fabric stock levels may vary.

‡ 2 S H Q Q H D V F W D U V S S U R [L P D R V H N X S V U H H F R P P H Q G H G

‡ Specifications V X E M H A F G W without notice. ©Fraser Shading Systems 2017



SheerWeave 2390 5% Fenestration Properties

Description	Colour	T _s	R _s	A _s	T _v	S/C (Internal)		
						1/8" C/L	1/4" C/L	1/4" H.A.
P12	Oyster	21	61	18	14	0.38	0.38	0.34
P13	Oyster/Beige	17	54	29	12	0.42	0.41	0.36
P14	Oyster/Pearl Grey	14	45	41	10	0.48	0.46	0.39
Q20	Beige	14	47	39	10	0.46	0.45	0.38
Q21	Beige/Pearl Grey	11	38	51	9	0.52	0.50	0.41
V20	Pearl Grey	10	31	59	9	0.57	0.54	0.43
V21	Charcoal	4	4	92	5	0.73	0.69	0.51
V22	Charcoal/Grey	5	9	86	6	0.70	0.67	0.49
V24	Charcoal/Chestnut	6	6	88	6	0.73	0.69	0.50
V32	Charcoal/Alpaca	7	18	75	9	0.65	0.62	0.47

KEY: T_s = Solar Transmittance, R_s = Solar Reflectance, A_s = Solar Absorption, T_v = Visible Transmittance

The solar optical properties are used to calculate the shading coefficient. The shading coefficient represents the percentage of solar heat gain that is transmitted to the interior through the glass and the shading system.

Darker colours provide maximum glare reduction and visibility. For complete technical information, current test results, performance specifications and larger samples, contact FSS

Specifications:

Composition:	35% Fiberglass, 65% Vinyl on Fiberglass
Openness factor:	Approximately 5%
Weight:	11.8 oz/yd ² (403 g/m ²)
Thickness:	.017 in (0.43mm)
Acoustical Value:	NRC .10 / SAA .12
Acoustical Performance:	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a.